

CHARACTER:

- 1.Physical performance
- a、Excellent mechanical properties
 - b、Excellent thermal stability
 - c、Low temperature soft good performance
 - d、Good flame retardancy
 - e、high of resistance to chemicals
 - f、Chemistry stability is good

2.Electrical Properties

- a、Electrical insulation good
- b、Good the dielectric properties

3.Processing properties

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、According to UL standard design

4.Environmental protection

- a、low smoke, non-halogen
- b、ROHS/REACH compliant


SHOULD BE USED:

Internal Wiring of Appliances

REFERENCE:

UL758-2010、UL1581-2009

Outline:



Wire structure description:
Conductor: Tinned /Bare copper ;
Insulation materials: XLPE Insulation

Internal wiring 。 Conductor temperature not over125℃ XLPE insulated wire
Rated temperature: 125℃ rated voltage: 600V

STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20℃ (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Nom.	Tole.
3298	16	26/0.254	14.60	1.50	1.15	1.04	3.80	±0.15
	18	16/0.254	23.20	1.17	1.15	1.04	3.45	±0.15
	20	21/0.18	36.70	0.95	1.15	1.04	3.25	±0.15

Marking: E211048  AWM STYLE 3298 NO.AWG 125℃ 600V XLPE QIFURUI 
AWM I A 125℃ 600V FT2 -LF-
OR: E211048  AWM STYLE 3298 NO. AWG 125℃ 600V XLPE QIFURUI 221756
CSA AWM I A 125℃ 600V FT2 -LF-

SAE COLOR SERIES

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

PACKAGE

*PACKAGE				
Part No.	Packing- FT/roll			
16-22AWG	☐ 200Ft	☐ 500Ft	☐ 1000Ft	☒ 2000Ft
According to customer requirements for packaging packaging				