

CHARACTER:

- 1.Physical performance
- a、Excellent mechanical properties

b、Excellent thermal stability

c、Low temperature soft good performance

d、Good flame retardancy

e、Of high resistance to chemicals

f、Chemistry stability is good

b、Good resistance to high temperature of the engine fluid

j、Excellent resistance to impact ability

2.Electrical Properties

- a、Electrical insulation good
- b、Good the dielectric properties

3.Processing properties

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、Good processing properties Harness
- d、Harness processing process good compatibility
- e、According to UL standard design

4.Environmental protection

- a、ROHS/REACH compliant

SHOULD BE USED:

As internal wiring or external interconnection in Class 2 Circuits of computers and electronic equipment.

REFERENCE:

UL758-2010、UL1581-2009

Outline:

Strands Tinned/Bare Copper

Shield

PVC Insulation

PVC Jacket

As internal wiring or external interconnection in
Class 2 Circuits of computers and electronic
equipment. UL2626

Wire structure description:

Conductor: Tinned /Bare copper ;

Insulation materials: PVC Insulation

Shield materials:tinned/bare copper or Aluminum foil warp (optional)

Jacket materials: PVC jacket

Internal or external wiring of electronic equipment , More than 80℃ environmen
temperature occasion
Rated temperature: 80℃ Rated voltage:30V

Part No.	Conductor				Insulation thickness (mm)		Jacket Thickness (mm)		Overall diameter (mm)		Conductor resistance 20℃ (Ω/Km)
	Cores No.	AWG	N0./ mm	Dia. mm	Nom.	Min Dia.	Nom.	Min	Nom.	min	
2626	2	26	7/0.16	0.48	0.25	0.98	0.76	0.61	3.88	3.58	150
	2	24	11/0.16	0.61	0.25	1.11	0.76	0.61	4.14	3.84	94.2
	2	22	17/0.16	0.76	0.25	1.26	0.76	0.61	4.43	4.13	59.4
	2	20	26/0.16	0.95	0.25	1.45	0.76	0.61	4.82	4.52	36.7
	3	26	7/0.16	0.48	0.25	0.98	0.76	0.61	3.88	3.58	150
	3	24	11/0.16	0.61	0.25	1.11	0.76	0.61	4.14	3.84	94.2
	3	22	17/0.16	0.76	0.25	1.26	0.76	0.61	4.43	4.13	59.4
	3	20	26/0.16	0.95	0.25	1.45	0.76	0.61	4.82	4.52	36.7
	4	28	7/0.127	0.38	0.25	0.88	0.76	0.61	3.95	3.65	239
	4	26	7/0.16	0.48	0.25	0.98	0.76	0.61	4.18	3.88	150
	5	28	7/0.127	0.38	0.25	0.88	0.76	0.61	4.19	3.89	239
	5	26	7/0.16	0.48	0.25	0.98	0.76	0.61	4.45	4.15	150
	6	28	7/0.127	0.38	0.25	0.88	0.76	0.61	4.41	4.11	239
	6	26	7/0.16	0.48	0.25	0.98	0.76	0.61	4.69	4.39	150
	7	28	7/0.127	0.38	0.25	0.88	0.76	0.61	4.61	4.31	239
	7	26	7/0.16	0.48	0.25	0.98	0.76	0.61	4.91	4.61	150

Note:shield thickness 0.20mm

Marking : E211048 AWM STYLE 2626 NO. AWG 80℃ 30V VW-1 PVC

QIFURUI cAWM 1A 80℃ 30V FT1 -LF-

SAE COLOR SERIES

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

PACKAGE

*PACKAGE				
Part No.	Packing- Ft/roll			
2~7	☐ 100Ft	☐ 500Ft	☒ 1000Ft	
According to customer requirements for packaging packaging				